

AD-A045 223

ARMY MISSILE RESEARCH AND DEVELOPMENT COMMAND REDSTO--ETC F/G 20/5
TARGET RECOGNITION USING MULTIPLE DISCRIMINANTS FROM AN INFRARE--ETC(U)
JUN 77 W E WEBB

UNCLASSIFIED


DRDMI-TE-77-16

NL


| OF |
AD
A045 223



END
DATE
FILMED
11-77
DDC



ADA 045223



**U.S. ARMY
MISSILE
RESEARCH
AND
DEVELOPMENT
COMMAND**



Redstone Arsenal, Alabama 35809

ADJ NO.
DDC FILE COPY

DMI FORM 1000, 1 APR 77


TECHNICAL REPORT TE-77-16

**TARGET RECOGNITION USING MULTIPLE DISCRIMINANTS
FROM AN INFRARED SENSOR**

Advanced Sensors Directorate
Technology Laboratory

24 June 1977

Approved for public release; distribution unlimited.



DISPOSITION INSTRUCTIONS

DESTROY THIS REPORT WHEN IT IS NO LONGER NEEDED. DO NOT RETURN IT TO THE ORIGINATOR.

DISCLAIMER

THE FINDINGS IN THIS REPORT ARE NOT TO BE CONSTRUED AS AN OFFICIAL DEPARTMENT OF THE ARMY POSITION UNLESS SO DESIGNATED BY OTHER AUTHORIZED DOCUMENTS.

TRADE NAMES

USE OF TRADE NAMES OR MANUFACTURERS IN THIS REPORT DOES NOT CONSTITUTE AN OFFICIAL INDORSEMENT OR APPROVAL OF THE USE OF SUCH COMMERCIAL HARDWARE OR SOFTWARE.

1. TITLE	
2. AUTHOR	
3. PERFORMING ORGANIZATION	
4. REPORT NUMBER	
5. DISTRIBUTION STATEMENT	
6. SUBJECT TERMS	
7. SECURITY CLASSIFICATION	
8. LIMITATION	
9. AVAILABILITY STATEMENT	
10. DISTRIBUTION STATEMENT	
11. PRICE	
12. NOTE	
13. ABSTRACT	
14. SUBJECT TERMS	
15. SECURITY CLASSIFICATION	
16. LIMITATION	
17. AVAILABILITY STATEMENT	
18. DISTRIBUTION STATEMENT	
19. PRICE	
20. NOTE	
21. ABSTRACT	
22. SUBJECT TERMS	
23. SECURITY CLASSIFICATION	
24. LIMITATION	
25. AVAILABILITY STATEMENT	
26. DISTRIBUTION STATEMENT	
27. PRICE	
28. NOTE	
29. ABSTRACT	
30. SUBJECT TERMS	
31. SECURITY CLASSIFICATION	
32. LIMITATION	
33. AVAILABILITY STATEMENT	
34. DISTRIBUTION STATEMENT	
35. PRICE	
36. NOTE	
37. ABSTRACT	
38. SUBJECT TERMS	
39. SECURITY CLASSIFICATION	
40. LIMITATION	
41. AVAILABILITY STATEMENT	
42. DISTRIBUTION STATEMENT	
43. PRICE	
44. NOTE	
45. ABSTRACT	
46. SUBJECT TERMS	
47. SECURITY CLASSIFICATION	
48. LIMITATION	
49. AVAILABILITY STATEMENT	
50. DISTRIBUTION STATEMENT	
51. PRICE	
52. NOTE	
53. ABSTRACT	
54. SUBJECT TERMS	
55. SECURITY CLASSIFICATION	
56. LIMITATION	
57. AVAILABILITY STATEMENT	
58. DISTRIBUTION STATEMENT	
59. PRICE	
60. NOTE	
61. ABSTRACT	
62. SUBJECT TERMS	
63. SECURITY CLASSIFICATION	
64. LIMITATION	
65. AVAILABILITY STATEMENT	
66. DISTRIBUTION STATEMENT	
67. PRICE	
68. NOTE	
69. ABSTRACT	
70. SUBJECT TERMS	
71. SECURITY CLASSIFICATION	
72. LIMITATION	
73. AVAILABILITY STATEMENT	
74. DISTRIBUTION STATEMENT	
75. PRICE	
76. NOTE	
77. ABSTRACT	
78. SUBJECT TERMS	
79. SECURITY CLASSIFICATION	
80. LIMITATION	
81. AVAILABILITY STATEMENT	
82. DISTRIBUTION STATEMENT	
83. PRICE	
84. NOTE	
85. ABSTRACT	
86. SUBJECT TERMS	
87. SECURITY CLASSIFICATION	
88. LIMITATION	
89. AVAILABILITY STATEMENT	
90. DISTRIBUTION STATEMENT	
91. PRICE	
92. NOTE	
93. ABSTRACT	
94. SUBJECT TERMS	
95. SECURITY CLASSIFICATION	
96. LIMITATION	
97. AVAILABILITY STATEMENT	
98. DISTRIBUTION STATEMENT	
99. PRICE	
100. NOTE	
101. ABSTRACT	
102. SUBJECT TERMS	
103. SECURITY CLASSIFICATION	
104. LIMITATION	
105. AVAILABILITY STATEMENT	
106. DISTRIBUTION STATEMENT	
107. PRICE	
108. NOTE	
109. ABSTRACT	
110. SUBJECT TERMS	
111. SECURITY CLASSIFICATION	
112. LIMITATION	
113. AVAILABILITY STATEMENT	
114. DISTRIBUTION STATEMENT	
115. PRICE	
116. NOTE	
117. ABSTRACT	
118. SUBJECT TERMS	
119. SECURITY CLASSIFICATION	
120. LIMITATION	
121. AVAILABILITY STATEMENT	
122. DISTRIBUTION STATEMENT	
123. PRICE	
124. NOTE	
125. ABSTRACT	
126. SUBJECT TERMS	
127. SECURITY CLASSIFICATION	
128. LIMITATION	
129. AVAILABILITY STATEMENT	
130. DISTRIBUTION STATEMENT	
131. PRICE	
132. NOTE	
133. ABSTRACT	
134. SUBJECT TERMS	
135. SECURITY CLASSIFICATION	
136. LIMITATION	
137. AVAILABILITY STATEMENT	
138. DISTRIBUTION STATEMENT	
139. PRICE	
140. NOTE	
141. ABSTRACT	
142. SUBJECT TERMS	
143. SECURITY CLASSIFICATION	
144. LIMITATION	
145. AVAILABILITY STATEMENT	
146. DISTRIBUTION STATEMENT	
147. PRICE	
148. NOTE	
149. ABSTRACT	
150. SUBJECT TERMS	
151. SECURITY CLASSIFICATION	
152. LIMITATION	
153. AVAILABILITY STATEMENT	
154. DISTRIBUTION STATEMENT	
155. PRICE	
156. NOTE	
157. ABSTRACT	
158. SUBJECT TERMS	
159. SECURITY CLASSIFICATION	
160. LIMITATION	
161. AVAILABILITY STATEMENT	
162. DISTRIBUTION STATEMENT	
163. PRICE	
164. NOTE	
165. ABSTRACT	
166. SUBJECT TERMS	
167. SECURITY CLASSIFICATION	
168. LIMITATION	
169. AVAILABILITY STATEMENT	
170. DISTRIBUTION STATEMENT	
171. PRICE	
172. NOTE	
173. ABSTRACT	
174. SUBJECT TERMS	
175. SECURITY CLASSIFICATION	
176. LIMITATION	
177. AVAILABILITY STATEMENT	
178. DISTRIBUTION STATEMENT	
179. PRICE	
180. NOTE	
181. ABSTRACT	
182. SUBJECT TERMS	
183. SECURITY CLASSIFICATION	
184. LIMITATION	
185. AVAILABILITY STATEMENT	
186. DISTRIBUTION STATEMENT	
187. PRICE	
188. NOTE	
189. ABSTRACT	
190. SUBJECT TERMS	
191. SECURITY CLASSIFICATION	
192. LIMITATION	
193. AVAILABILITY STATEMENT	
194. DISTRIBUTION STATEMENT	
195. PRICE	
196. NOTE	
197. ABSTRACT	
198. SUBJECT TERMS	
199. SECURITY CLASSIFICATION	
200. LIMITATION	
201. AVAILABILITY STATEMENT	
202. DISTRIBUTION STATEMENT	
203. PRICE	
204. NOTE	
205. ABSTRACT	
206. SUBJECT TERMS	
207. SECURITY CLASSIFICATION	
208. LIMITATION	
209. AVAILABILITY STATEMENT	
210. DISTRIBUTION STATEMENT	
211. PRICE	
212. NOTE	
213. ABSTRACT	
214. SUBJECT TERMS	
215. SECURITY CLASSIFICATION	
216. LIMITATION	
217. AVAILABILITY STATEMENT	
218. DISTRIBUTION STATEMENT	
219. PRICE	
220. NOTE	
221. ABSTRACT	
222. SUBJECT TERMS	
223. SECURITY CLASSIFICATION	
224. LIMITATION	
225. AVAILABILITY STATEMENT	
226. DISTRIBUTION STATEMENT	
227. PRICE	
228. NOTE	
229. ABSTRACT	
230. SUBJECT TERMS	
231. SECURITY CLASSIFICATION	
232. LIMITATION	
233. AVAILABILITY STATEMENT	
234. DISTRIBUTION STATEMENT	
235. PRICE	
236. NOTE	
237. ABSTRACT	
238. SUBJECT TERMS	
239. SECURITY CLASSIFICATION	
240. LIMITATION	
241. AVAILABILITY STATEMENT	
242. DISTRIBUTION STATEMENT	
243. PRICE	
244. NOTE	
245. ABSTRACT	
246. SUBJECT TERMS	
247. SECURITY CLASSIFICATION	
248. LIMITATION	
249. AVAILABILITY STATEMENT	
250. DISTRIBUTION STATEMENT	
251. PRICE	
252. NOTE	
253. ABSTRACT	
254. SUBJECT TERMS	
255. SECURITY CLASSIFICATION	
256. LIMITATION	
257. AVAILABILITY STATEMENT	
258. DISTRIBUTION STATEMENT	
259. PRICE	
260. NOTE	
261. ABSTRACT	
262. SUBJECT TERMS	
263. SECURITY CLASSIFICATION	
264. LIMITATION	
265. AVAILABILITY STATEMENT	
266. DISTRIBUTION STATEMENT	
267. PRICE	
268. NOTE	
269. ABSTRACT	
270. SUBJECT TERMS	
271. SECURITY CLASSIFICATION	
272. LIMITATION	
273. AVAILABILITY STATEMENT	
274. DISTRIBUTION STATEMENT	
275. PRICE	
276. NOTE	
277. ABSTRACT	
278. SUBJECT TERMS	
279. SECURITY CLASSIFICATION	
280. LIMITATION	
281. AVAILABILITY STATEMENT	
282. DISTRIBUTION STATEMENT	
283. PRICE	
284. NOTE	
285. ABSTRACT	
286. SUBJECT TERMS	
287. SECURITY CLASSIFICATION	
288. LIMITATION	
289. AVAILABILITY STATEMENT	
290. DISTRIBUTION STATEMENT	
291. PRICE	
292. NOTE	
293. ABSTRACT	
294. SUBJECT TERMS	
295. SECURITY CLASSIFICATION	
296. LIMITATION	
297. AVAILABILITY STATEMENT	
298. DISTRIBUTION STATEMENT	
299. PRICE	
300. NOTE	
301. ABSTRACT	
302. SUBJECT TERMS	
303. SECURITY CLASSIFICATION	
304. LIMITATION	
305. AVAILABILITY STATEMENT	
306. DISTRIBUTION STATEMENT	
307. PRICE	
308. NOTE	
309. ABSTRACT	
310. SUBJECT TERMS	
311. SECURITY CLASSIFICATION	
312. LIMITATION	
313. AVAILABILITY STATEMENT	
314. DISTRIBUTION STATEMENT	
315. PRICE	
316. NOTE	
317. ABSTRACT	
318. SUBJECT TERMS	
319. SECURITY CLASSIFICATION	
320. LIMITATION	
321. AVAILABILITY STATEMENT	
322. DISTRIBUTION STATEMENT	
323. PRICE	
324. NOTE	
325. ABSTRACT	
326. SUBJECT TERMS	
327. SECURITY CLASSIFICATION	
328. LIMITATION	
329. AVAILABILITY STATEMENT	
330. DISTRIBUTION STATEMENT	
331. PRICE	
332. NOTE	
333. ABSTRACT	
334. SUBJECT TERMS	
335. SECURITY CLASSIFICATION	
336. LIMITATION	
337. AVAILABILITY STATEMENT	
338. DISTRIBUTION STATEMENT	
339. PRICE	
340. NOTE	
341. ABSTRACT	
342. SUBJECT TERMS	
343. SECURITY CLASSIFICATION	
344. LIMITATION	
345. AVAILABILITY STATEMENT	
346. DISTRIBUTION STATEMENT	
347. PRICE	
348. NOTE	
349. ABSTRACT	
350. SUBJECT TERMS	
351. SECURITY CLASSIFICATION	
352. LIMITATION	
353. AVAILABILITY STATEMENT	
354. DISTRIBUTION STATEMENT	
355. PRICE	
356. NOTE	
357. ABSTRACT	
358. SUBJECT TERMS	
359. SECURITY CLASSIFICATION	
360. LIMITATION	
361. AVAILABILITY STATEMENT	
362. DISTRIBUTION STATEMENT	
363. PRICE	
364. NOTE	
365. ABSTRACT	
366. SUBJECT TERMS	
367. SECURITY CLASSIFICATION	
368. LIMITATION	
369. AVAILABILITY STATEMENT	
370. DISTRIBUTION STATEMENT	
371. PRICE	
372. NOTE	
373. ABSTRACT	
374. SUBJECT TERMS	
375. SECURITY CLASSIFICATION	
376. LIMITATION	
377. AVAILABILITY STATEMENT	
378. DISTRIBUTION STATEMENT	
379. PRICE	
380. NOTE	
381. ABSTRACT	
382. SUBJECT TERMS	
383. SECURITY CLASSIFICATION	
384. LIMITATION	
385. AVAILABILITY STATEMENT	
386. DISTRIBUTION STATEMENT	
387. PRICE	
388. NOTE	
389. ABSTRACT	
390. SUBJECT TERMS	
391. SECURITY CLASSIFICATION	
392. LIMITATION	
393. AVAILABILITY STATEMENT	
394. DISTRIBUTION STATEMENT	
395. PRICE	
396. NOTE	
397. ABSTRACT	
398. SUBJECT TERMS	
399. SECURITY CLASSIFICATION	
400. LIMITATION	
401. AVAILABILITY STATEMENT	
402. DISTRIBUTION STATEMENT	
403. PRICE	
404. NOTE	
405. ABSTRACT	
406. SUBJECT TERMS	
407. SECURITY CLASSIFICATION	
408. LIMITATION	
409. AVAILABILITY STATEMENT	
410. DISTRIBUTION STATEMENT	
411. PRICE	
412. NOTE	
413. ABSTRACT	
414. SUBJECT TERMS	
415. SECURITY CLASSIFICATION	
416. LIMITATION	
417. AVAILABILITY STATEMENT	
418. DISTRIBUTION STATEMENT	
419. PRICE	
420. NOTE	
421. ABSTRACT	
422. SUBJECT TERMS	
423. SECURITY CLASSIFICATION	
424. LIMITATION	
425. AVAILABILITY STATEMENT	
426. DISTRIBUTION STATEMENT	
427. PRICE	
428. NOTE	
429. ABSTRACT	
430. SUBJECT TERMS	
431. SECURITY CLASSIFICATION	
432. LIMITATION	
433. AVAILABILITY STATEMENT	
434. DISTRIBUTION STATEMENT	
435. PRICE	
436. NOTE	
437. ABSTRACT	
438. SUBJECT TERMS	
439. SECURITY CLASSIFICATION	
440. LIMITATION	
441. AVAILABILITY STATEMENT	
442. DISTRIBUTION STATEMENT	
443. PRICE	
444. NOTE	
445. ABSTRACT	
446. SUBJECT TERMS	
447. SECURITY CLASSIFICATION	
448. LIMITATION	
449. AVAILABILITY STATEMENT	
450. DISTRIBUTION STATEMENT	
451. PRICE	
452. NOTE	
453. ABSTRACT	
454. SUBJECT TERMS	
455. SECURITY CLASSIFICATION	
456. LIMITATION	
457. AVAILABILITY STATEMENT	
458. DISTRIBUTION STATEMENT	
459. PRICE	
460. NOTE	
461. ABSTRACT	
462. SUBJECT TERMS	
463. SECURITY CLASSIFICATION	
464. LIMITATION	
465. AVAILABILITY STATEMENT	
466. DISTRIBUTION STATEMENT	
467. PRICE	
468. NOTE	
469. ABSTRACT	
470. SUBJECT TERMS	
471. SECURITY CLASSIFICATION	
472. LIMITATION	
473. AVAILABILITY STATEMENT	
474. DISTRIBUTION STATEMENT	
475. PRICE	
476. NOTE	
477. ABSTRACT	
478. SUBJECT TERMS	
479. SECURITY CLASSIFICATION	
480. LIMITATION	
481. AVAILABILITY STATEMENT	
482. DISTRIBUTION STATEMENT	
483. PRICE	
484. NOTE	
485. ABSTRACT	
486. SUBJECT TERMS	
487. SECURITY CLASSIFICATION	
488. LIMITATION	
489. AVAILABILITY STATEMENT	
490. DISTRIBUTION STATEMENT	
491. PRICE	
492. NOTE	
493. ABSTRACT	
494. SUBJECT TERMS	
495. SECURITY CLASSIFICATION	
496. LIMITATION	
497. AVAILABILITY STATEMENT	
498. DISTRIBUTION STATEMENT	
499. PRICE	
500. NOTE	
501. ABSTRACT	
502. SUBJECT TERMS	
503. SECURITY CLASSIFICATION	
504. LIMITATION	
505. AVAILABILITY STATEMENT	
506. DISTRIBUTION STATEMENT	
507. PRICE	
508. NOTE	
509. ABSTRACT	
510. SUBJECT TERMS	
511. SECURITY CLASSIFICATION	
512. LIMITATION	
513. AVAILABILITY STATEMENT	
514. DISTRIBUTION STATEMENT	
515. PRICE	
516. NOTE	
517. ABSTRACT	
518. SUBJECT TERMS	
519. SECURITY CLASSIFICATION	
520. LIMITATION	
521. AVAILABILITY STATEMENT	
522. DISTRIBUTION STATEMENT	
523. PRICE	
524. NOTE	
525. ABSTRACT	
526. SUBJECT TERMS	
527. SECURITY CLASSIFICATION	
528. LIMITATION	
529. AVAILABILITY STATEMENT	
530. DISTRIBUTION STATEMENT	
531. PRICE	
532. NOTE	
533. ABSTRACT	
534. SUBJECT TERMS	
535. SECURITY CLASSIFICATION	
536. LIMITATION	
537. AVAILABILITY STATEMENT	
538. DISTRIBUTION STATEMENT	
539. PRICE	
540. NOTE	
541. ABSTRACT	
542. SUBJECT TERMS	
543. SECURITY CLASSIFICATION	
544. LIMITATION	
545. AVAILABILITY STATEMENT	
546. DISTRIBUTION STATEMENT	
547. PRICE	
548. NOTE	
549. ABSTRACT	
550. SUBJECT TERMS	
551. SECURITY CLASSIFICATION	
552. LIMITATION	
553. AVAILABILITY STATEMENT	
554. DISTRIBUTION STATEMENT	
555. PRICE	
556. NOTE	
557. ABSTRACT	
558. SUBJECT TERMS	
559. SECURITY CLASSIFICATION	
560. LIMITATION	
561. AVAILABILITY STATEMENT	
562. DISTRIBUTION STATEMENT	
563. PRICE	
564. NOTE	
565. ABSTRACT	
566. SUBJECT TERMS	
567. SECURITY CLASSIFICATION	
568. LIMITATION	
569. AVAILABILITY STATEMENT	
570. DISTRIBUTION STATEMENT	
571. PRICE	
572. NOTE	
573. ABSTRACT	
574. SUBJECT TERMS	
575. SECURITY CLASSIFICATION	
576. LIMITATION	
577. AVAILABILITY STATEMENT	
578. DISTRIBUTION STATEMENT	
579. PRICE	
580. NOTE	
581. ABSTRACT	
582. SUBJECT TERMS	
583. SECURITY CLASSIFICATION	
584. LIMITATION	
585. AVAILABILITY STATEMENT	
586. DISTRIBUTION STATEMENT	
587. PRICE	
588. NOTE	
589. ABSTRACT	
590. SUBJECT TERMS	
591. SECURITY CLASSIFICATION	
592. LIMITATION	
593. AVAILABILITY STATEMENT	
594. DISTRIBUTION STATEMENT	
595. PRICE	
596. NOTE	
597. ABSTRACT	
598. SUBJECT TERMS	
599. SECURITY CLASSIFICATION	
600. LIMITATION	
601. AVAILABILITY STATEMENT	
602. DISTRIBUTION STATEMENT	
603. PRICE	
604. NOTE	
605. ABSTRACT	
606. SUBJECT TERMS	
607. SECURITY CLASSIFICATION	
608. LIMITATION	
609. AVAILABILITY STATEMENT	
610. DISTRIBUTION STATEMENT	
611. PRICE	
612. NOTE	
613. ABSTRACT	
614. SUBJECT TERMS	
615. SECURITY CLASSIFICATION	
616. LIMITATION	
617. AVAILABILITY STATEMENT	
618. DISTRIBUTION STATEMENT	
619. PRICE	
620. NOTE	
621. ABSTRACT	
622. SUBJECT TERMS	
623. SECURITY CLASSIFICATION	

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER DRDMI-TE-77-16	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) TARGET RECOGNITION USING MULTIPLE DISCRIMINANTS FROM AN INFRARED SEEKER	5. TYPE OF REPORT & PERIOD COVERED Technical Report	
7. AUTHOR(s) William E. Webb	6. PERFORMING ORG. REPORT NUMBER TE-77-16	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Commander US Army Missile Research and Development Command Attn: DRDMI-TE Redstone Arsenal, ACabama 35809	8. CONTRACT OR GRANT NUMBER(s)	
11. CONTROLLING OFFICE NAME AND ADDRESS Commander US Army Missile Research and Development Command Attn: DRDMI-TI Redstone Arsenal, Alabama 35809	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 1L362303A214 AMCMS 632303.2140311.04	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	12. REPORT DATE 11 24 Jun 77	
	13. NUMBER OF PAGES 20	
	15. SECURITY CLASS. (of this report) UNCLASSIFIED	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Statistical methods Multivariate statistical analysis Automatic target recognition		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) It has been suggested that a laser designator could be adapted to measure certain characteristics of the object being designated and that these measurements could be a useful aid in target recognition and/or identification. Characteristics that could be measured include size, motion (speed), vibration, and quantities relating to the target surface such as reflectance, depolarization, etc. Unfortunately, it appears unlikely that any single target		

ABSTRACT (Continued)

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

410143

ABSTRACT (Continued)

characteristic will be sufficiently unique to provide an unequivocal identification.

In this report, consideration is given to statistical methods for combining several target characteristics to enhance the identification capability. The technique studied involves using multivariate statistical analysis to construct a linear or quadratic discriminant function on the various measured quantities. It is shown that using this approach, an automatic target recognition feature could be implemented at very small additional cost.

The final section of this report details the experimental data needed to assess completely the feasibility of the proposed identification aid and recommends an experimental program for collecting these data.



CONTENTS

	Page
I. INTRODUCTION	3
II. STATEMENT OF THE PROBLEM	5
III. STATISTICAL CLASSIFICATION	5
IV. CASE OF UNEQUAL COVARIANCE MATRICES	9
V. APPLICATION TO A LASER IDENTIFICATION AID	10
VI. RECOMMENDATIONS FOR AN EXPERIMENTAL RESEARCH PROGRAM . . .	13
REFERENCES	18

RE: Technical Report TE-77-16
Classified references-
DDC should accession and document
should remain for unlimited distribut-
ion per Mr. Moody, Army Missile Comd

I. INTRODUCTION

It is well established that long wavelength infrared radiations are better able to penetrate rain, smoke, and haze than are either visible or near infrared radiations. Because of the greater penetrating power at the longer wavelength, it appears likely that future laser terminal homing systems may operate either in the 3- to 5- μ m, or the 8- to 14- μ m regions of the spectrum [1]. Furthermore, it seems likely that under conditions of reduced visibility, the effective range of these systems may be determined by the operator's ability to locate and designate a target rather than by the ability of the homing seeker to track through smoke or fog [1,2,3,4]. For this reason, it seems desirable that the designator operator be provided with some means of target location and recognition other than visual sighting.

Recently, studies have been conducted to determine the technical feasibility of incorporating a recognition aid directly into a terminal homing laser designator [5,6]. It has been shown that the reflected laser beam contains a considerable amount of information about the reflecting object which, with proper processing, could be used to distinguish a military target from an extraneous or militarily unimportant object. Among the characteristics of the reflected laser beam which could be used as target discriminant are the following:

- a) Moving Target Indicator (MTI) - Laser radiation reflected from a moving target experiences a frequency shift (Doppler shift) proportional to the radial speed of the target. By using heterodyne detection, this frequency shift can be measured, thus providing a measurement of the target's speed toward or away from the designator.
- b) Vibration Signatures - Vibration of the target will produce a Doppler shift in the reflected laser beam. The frequency spreading associated with the vibratory motion could provide a characteristic signature from which the target could be recognized. It is believed that the vibration signature may prove to be the most useful discriminant [6].
- c) Size Estimation - By scanning the designator beam across the target, it is possible to estimate the target's size. The accuracy of this estimation is determined by the width of the laser beam at the target and the contrast between target and background.
- d) Other Discriminants - Other target discriminants which might be used include the strength of the reflected signal, degree of depolarization of the reflected radiation, and laser speckle effects.

As it is presently envisioned, the recognition aid would use the designator to illuminate the target and might, in a lock-before-launch configuration, use the missile tracking system's sensors to measure one of the previously mentioned quantities. If lock-before-launch were not possible, or if the missile were launched from somewhere other than the

designator, then an additional sensor would be required. In either case, the recognition aid is conceived as a relatively low cost add-on to the basic designator-guidance system.

It should be emphasized that the system as presently envisioned will not necessarily provide a means of absolute target identification because none of the proposed discriminants are sufficiently unique.* For example, if a system were devised that could measure the size of an object being designated with a fair degree of precision, and if it were found that a suspected target's size were comparable with that of an enemy tank, this would be useful information. However, it would not be sufficient to insure that the suspected target were, in fact, a tank. It could be a large truck, a small building, or even a pile of scrap metal.

It has been proposed that a more positive identification could be obtained by using two or more of the previously mentioned discriminants. To continue this example, if it were known that the tank-size object were moving, the building and scrap heap could be eliminated. The remaining possibilities are a tank, a tank-size truck, or perhaps a small truck viewed from the side which had approximately the same dimension as the frontal aspect of a tank. In any case, the identification is more certain than would be the case with either a size measurement or MTI alone.

This report considers how an identification system might be implemented using two or more discriminants. This problem can be divided into two parts: first, what measurements should be made; second, once the measurements are made, how can they be used in deciding if a suspected target should be attacked? The first question has been addressed elsewhere [5,6]. The second question is basically a problem in multivariate statistical analysis, and will be the principle subject of this report.

*The possible exception to this statement is vibration signatures which may or may not be sufficiently unique to provide a means of positive identification. At the present time, information is not sufficient concerning the actual signatures of military vehicles and the precision with which they can be measured optically to assess their usefulness fully in target identification. However, on the basis of the available data, there is considerable optimism about the possibility that they may provide a practical means of positive target identification.

II. STATEMENT OF THE PROBLEM

It is assumed that a laser designator-system is instrumented to measure a number of quantities $(X_1, X_2, X_3, \dots, X_n)$. For example, X_1 might be the horizontal dimension of the target, X_2 the radial component of the target's speed, etc. If target vibration measurements are included, then some of the quantities might be derived from the audio spectrum of the target. One possibility would be to let X_k be the fraction of the total audio power in the frequency bandwidth f_k to $f_k + \Delta f_k$. Other possibilities also exist and will be discussed later; for now, it is assumed that the quantities to be measured have been selected and that the instrumentation for making the measurements is in hand. A little reflection will show that the X 's are a set of random variables. Randomness is introduced into the measurements for two reasons. First, there are random errors in all measurements and, as shown by analysis in previous reports, these may be considerable for the measurements being considered here. Secondly, even if there were no measurement errors, some of the quantities would still be random variables due to changes in the conditions under which the measurements are made. For example, the apparent size of a tank will depend on the aspect angle. The vibration will depend upon the target's speed or it may vary from one vehicle to another of the same type. Furthermore, it is clear that, in general, the X 's will not be statistically independent.

Now, the problem may be stated as follows: Given a set of measurements (X_1, X_2, \dots, X_n) made on a suspected target, a decision must be made in some optimum fashion whether the object is an actual target or not. There is a standard problem in statistical decision theory, a solution of which will be presented in the following section.

III. STATISTICAL CLASSIFICATION

It is assumed that a set of measurements (X_1, X_2, \dots, X_n) has been made on an object which is known to be a member of one of two populations; T a target or \bar{T} , a nontarget. For convenience the measurements will be denoted by a point

$$\vec{X} = (X_1, X_2, X_3, \dots, X_n) \quad (1)$$

in an n -dimensional measurement space M . Furthermore, M is divided into two regions R_T and $R_{\bar{T}}$ such that if $\vec{X} \in R_T$ the object will be considered a target, and if $\vec{X} \in R_{\bar{T}}$, the object will be considered a nontarget. Clearly, the union $R_T \cup R_{\bar{T}}$ must be M . Also, it is assumed

that $P_T(\vec{x})$ and $P_{\bar{T}}(\vec{x})$ are the population densities of targets and nontargets. The following conditional probabilities may then be defined:

- a) The probability of correctly classifying a target:

$$P(T|T, R) = \int_{R_T} P_T(\vec{x}) d\vec{x} \quad . \quad (2)$$

- b) The probability of correctly classifying a nontarget:

$$P(\bar{T}|\bar{T}, R) = \int_{R_{\bar{T}}} P_{\bar{T}}(\vec{x}) d\vec{x} \quad . \quad (3)$$

- c) The probabilities of incorrectly classifying a target and a nontarget:

$$P(\bar{T}|T, R) = \int_{R_{\bar{T}}} P_T(\vec{x}) d\vec{x} \quad (4)$$

$$P(T|\bar{T}, R) = \int_{R_T} P_{\bar{T}}(\vec{x}) d\vec{x} \quad . \quad (5)$$

Now it is assumed that there is a cost of $C(T|\bar{T})$ associated with classifying a nontarget as a target and a cost $C(\bar{T}|T)$ associated with calling a target a nontarget. Then, the expected loss due to misclassification is

$$L = C(\bar{T}|T)P(\bar{T}|T, R)P(T) + C(T|\bar{T})P(T|\bar{T}, R)P(\bar{T}) \quad (6)$$

where $P(T)$ and $P(\bar{T})$ are the a priori probabilities of the object being a target or a nontarget, respectively. The optimum decision procedure is the one which minimizes this loss. Such a procedure is called a Bayes procedure. Clearly, the mathematical problem is to choose R_T such that L is minimum. This problem has been treated in the literature [7,8]. It can be shown that the regions of classification which minimize L are:

$$R_T : \frac{P_T(\bar{x})}{P_{\bar{T}}(\bar{x})} > k \quad (7)$$

where

$$k = P(\bar{T})C(T|\bar{T})/P(\bar{T})C(\bar{T}|T) \quad (8)$$

That is to say that if for a given \bar{X} the ratio $P_T/P_{\bar{T}}$ is greater than k , the object is classified as a target and not otherwise.

The treatment to this point has been quite general. Now, it is necessary to make some assumptions concerning the probabilities $P_T(\bar{X})$ and $P_{\bar{T}}(\bar{X})$. The common, but often questionable, assumption is that of multivariate normal populations. With this assumption, the following equation can be written:

$$P_i(\vec{X}) = (2\pi)^{-N/2} |\Sigma|^{-1/2} \exp \left[-\frac{1}{2} \left(\vec{x} - \mu^{(i)} \right)' \Sigma^{-1} \left(\vec{x} - \mu^{(i)} \right) \right] \quad (9)$$

where $\mu^{(i)}$ is the vector of means of the i^{th} population, and Σ is the covariance matrix, i.e.,

$$\vec{\mu}^{(i)} = (\mu_1, \mu_2, \dots, \mu_N) \quad (10)$$

$$\Sigma = \begin{pmatrix} \sigma_1^2 & \rho_{12}\sigma_1\sigma_2 & \dots \\ \rho_{21}\sigma_1\sigma_2 & \sigma_2^2 & \dots \\ & & \dots \end{pmatrix} \quad (11)$$

Here, $\sigma_1, \sigma_2, \dots$ are the variance of the X 's and ρ_{ij} is the correlation coefficient between X_1 and X_j . Σ is assumed to be the same for both targets and nontargets populations. Finally, i may take on the values 1 or 2 corresponding to the target and nontarget populations, respectively. Substituting Equation (9) into Equation (7) and taking the logarithm of both sides, the following is obtained:

$$-\frac{1}{2} \left[\left(\bar{X} - \bar{\mu}^{(1)} \right)' \Sigma^{-1} \left(\bar{X} - \bar{\mu}^{(1)} \right) - \left(\bar{X} - \bar{\mu}^{(2)} \right)' \Sigma^{-1} \left(\bar{X} - \bar{\mu}^{(2)} \right) \right] \geq \ln k \quad (12)$$

for the region of classification as a target. On expanding the left side and rearranging terms, this becomes

$$\bar{X}' \Sigma^{-1} \left(\bar{\mu}^{(1)} - \bar{\mu}^{(2)} \right) - \frac{1}{2} \left(\mu^{(1)} + \mu^{(2)} \right)' \Sigma^{-1} \left(\mu^{(1)} - \mu^{(2)} \right) \geq \ln k \quad (13)$$

Equation (13) is a linear equation in the X_j . Therefore, it may be written in the form

$$a_1 x_1 + a_2 x_2 + \dots + a_N x_N \geq \ln k + \frac{1}{2} b \quad (14)$$

where a_j is the j^{th} component of the vector

$$\Sigma^{-1} \left(\bar{\mu}^{(1)} - \bar{\mu}^{(2)} \right)$$

and b is

$$\left(\bar{\mu}^{(1)} + \bar{\mu}^{(2)} \right)' \Sigma^{-1} \left(\bar{\mu}^{(1)} - \bar{\mu}^{(2)} \right)$$

The left side of the equation is called the discriminant function. If the population means (μ_1 and μ_2) and the covariance matrix Σ are known, it is merely necessary to evaluate the discriminant function; then, if the inequality of Equation (14) is satisfied, the object is classified as having come from Population 1 (target); if not, it is classified as having come from Population 2 (nontarget).

The previously outlined procedure can be generalized to allow classification into more than two populations. If $n - 1$ different types of targets are to be considered, $i = 1$ represents targets of the first type; $i = 2$, targets of the second type; and so on to $i = n - 1$. Nontargets are then represented by $i = n$. Then, proceeding as before, a system of linear discriminate functions $\mu_j(x)$ can be constructed as follows:

$$\mu_{ij} = \frac{P_i(x)}{P_j(x)} \quad (15)$$

from which a system of inequalities of the form

$$\mu_{ij} > \text{constants} \quad (16)$$

is obtained. Classification can be made on the basis of this system. In the remainder of this report, classification into more than two populations will not be considered.

The probability of classification errors using this procedure has been extensively investigated [7,9,10]. It can be shown that the probability of misclassification can be computed in terms of Hotelling's T^2 statistic; however, a discussion of this aspect of the problem is beyond the scope of this report.

IV. CASE OF UNEQUAL COVARIANCE MATRICES

The discussions of classification by means of multivariate statistical analyzes that are found in the literature assume equal covariance matrices for the different populations. This assumption is convenient in that it leads to a linear discriminant function. However, it is difficult to justify at best. In many cases, it is obviously wrong. In this section, a discriminant function is derived under the assumption $\Sigma^{(1)} \neq \Sigma^{(2)}$ where $\Sigma^{(1)}$ and $\Sigma^{(2)}$ are the covariance matrices of the target and nontarget populations.

For the case of unequal covariance matrices, Equation (12) becomes

$$\frac{1}{2} \left[\left(\bar{X} - \bar{\mu}^{(1)} \right)' \Sigma^{(1)-1} \left(\bar{X} - \bar{\mu}^{(1)} \right) - \left(\bar{X} - \bar{\mu}^{(2)} \right)' \Sigma^{(2)-1} \left(\bar{X} - \bar{\mu}^{(2)} \right) \right] \geq \ln k \quad (17)$$

or

$$\begin{aligned} -\frac{1}{2} \left[X' \Sigma^{(1)-1} X - X' \Sigma^{(1)-1} \mu^{(1)} - \mu^{(1)'} \Sigma^{(1)-1} X \right. \\ \left. + \mu^{(1)'} \Sigma^{(1)-1} \mu^{(1)} - X' \Sigma^{(2)-1} X \right. \\ \left. + X' \Sigma^{(2)-1} \mu^{(2)} + \mu^{(2)'} \Sigma^{(2)-1} X \right. \\ \left. - \mu^{(2)'} \Sigma^{(2)-1} \mu^{(2)} \right] \geq \ln k \quad ; \quad (18) \end{aligned}$$

hence, the discriminate function:

$$\begin{aligned} \frac{1}{2} X' \left(\Sigma^{(1)-1} - \Sigma^{(2)-1} \right) X - X' \left(\Sigma^{(1)-1} \mu^{(1)} - \Sigma^{(2)-1} \mu^{(2)} \right) \\ + \frac{1}{2} \left(\mu^{(1)'} \Sigma^{(1)-1} \mu^{(2)'} - \mu^{(2)'} \Sigma^{(2)-1} \mu^{(1)} \right) \geq \ln k \end{aligned} \quad (19)$$

For unequal variances, the discriminate function is quadratic. In principle, this should cause no difficulty except for an increase in the computational effort required to evaluate the function. The classification errors arising from the application of quadratic forms has not been extensively studied [11].

V. APPLICATION TO A LASER IDENTIFICATION AID

The Bayes procedure in the previous sections provides a formal solution to the problem of target classification; however, the question of its applicability to a laser identification aid remains. In this section, some of the problems in applying this technique will be discussed.

A. Mathematical Assumptions

The Bayes procedure is based on two assumptions: (1) the explicit assumption of multivariate normal populations, and (2) a tacit assumption that the population means are sufficiently different to allow classification at all. The assumption of normal populations is commonly made in most classification problems, although it is often questionable. For many of the discriminants considered here, it seems likely that they will not be normal variables. However, it is not known at this time what distribution should be used. If it were known, it is likely that any other distribution function would lead to intractable mathematics. It seems, therefore, that the assumption of normal statistics must be used by default, at least for the present. Fortunately, it has been found that in many cases (drawn mostly from the behavioral and life sciences) that the assumption of a multivariate normal distribution often yields satisfactory results even when it is known that the true population densities are not normal.

The validity of the second assumption, namely, that the population means are sufficiently different to allow classification, is also difficult to assess at this time. If for any one discriminant variable the difference in means between target and nontarget populations is sufficiently large (several times the variance), then this variable alone would be sufficient for classification. However, if the differences in means of all variables are very small, then the use of

multivariate analysis will not be of much value. It is in the intermediate case, (i.e., when there is a significant difference in the means, but this difference is still not large enough to allow accurate classification with a single variable) that the multivariate approach is useful. Thus, a knowledge of the mean and variances of both target and nontarget populations is needed to assess whether or not classification by discriminant function is appropriate. This information is not available at the present time.

B. Selection of Measurements to be Used for Classification

Although any of the measurements discussed in Section I could be used for target identification, it is clear that the minimum number consistent with accurate classification should be used. Which measurements are chosen will depend upon the effectiveness of the variable in classification and the difficulty of implementing the measurement. A considerable amount of experimental data will be required before this choice can be made with certainty.

C. Determination of the Population Means and the Covariance Matrix

To construct the discriminant function, it will be necessary to determine accurately the mean and variance of each variable used in the classification. This must be done for both target and nontarget populations. Furthermore, it will be necessary to determine the correlation coefficients for those variables that are not statistically independent. In principle, these quantities can be estimated by making a large number of measurements on typical targets and nontargets. If N_T measurements $(\vec{X}_i^{(1)})$ from targets and $N_{\bar{T}}$ measurement $(\vec{X}_j^{(2)})$ from nontargets are used; then the mean vectors $\vec{\mu}^{(1)}$, and $\vec{\mu}^{(2)}$ would be estimated by $\langle \vec{X}^{(1)} \rangle$ and $\langle \vec{X}^{(2)} \rangle$ where

$$\langle \vec{X}^{(1)} \rangle = \frac{1}{N_T} \sum_{\alpha=1}^{N_T} \vec{X}_{\alpha}^{(1)} \quad (20)$$

$$\langle \vec{X}^{(2)} \rangle = \frac{1}{N_{\bar{T}}} \sum_{\alpha=1}^{N_{\bar{T}}} \vec{X}_{\alpha}^{(2)} \quad (21)$$

The covariance matrix would be estimated by S given by

$$(N_T + N_{\bar{T}} - 2)S = \sum_{\alpha=1}^{N_T} (\vec{X}_{\alpha}^{(1)} - \langle \vec{X}^{(1)} \rangle)(\vec{X}_{\alpha}^{(1)} - \langle \vec{X}^{(1)} \rangle)' + \sum_{\alpha=1}^{N_T} (\vec{X}_{\alpha}^{(2)} - \langle \vec{X}^{(2)} \rangle)(\vec{X}_{\alpha}^{(2)} - \langle \vec{X}^{(2)} \rangle)' \quad (22)$$

Clearly, this will require a very large amount of experimental data. Furthermore, the nontarget population presents a particular problem because it will be necessary to insure that the objects used in estimating the statistical parameters are representative of nontargets that will be encountered in an actual battlefield situation.

The problem of obtaining representative populations for parameter estimation can be simplified if it can be assumed that in practice the designator operator will exercise a certain amount of judgment and not simply designate objects at random. It would then be possible to restrict the class of nontargets to certain well-defined objects. For example, it might be assumed in a certain situation that the target would be a tank or a armored personnel carrier (APC) and that a nontarget would always be another vehicle.

D. Estimation of A Priori Probabilities and Misclassification Cost

The discriminant function involves both the a priori probabilities that an object being designated is a target and a misclassification cost factor, neither of which are known accurately. The determination of the cost (or expected loss) associated with attacking a false target, or failing to attack a real target, is largely a matter of military judgment; as such it is outside the scope of this report.

There are several possible ways in which an estimation of the a priori probability of designating a target might be made. The simplest way (and one frequently used when the actual probabilities are unknown) is to assume that the probabilities of designating a target or a nontarget are equal, i.e.,

$$P(T) = P(\bar{T}) = \frac{1}{2} \quad (23)$$

Although this assumption has some validity, Anderson [7] has shown by an example that the probability of misclassification will be much greater than it would be the case if the actual a priori probabilities were known.

In some cases, it may be possible to improve upon the assumption of equal probabilities by postulating the tactical situation in which the identification aid will be used. As a hypothetical example, it is assumed that the designator is being used in a defensive position under attack by enemy armor. As before, it is assumed that the suspected target will be a vehicle and that only tanks are to be attacked. The problem is then simplified to distinguishing between tanks and other vehicles. Now, if there is information concerning the mix of tanks and other vehicles in a typical enemy armor attack, it would be reasonable to use this ratio for the a priori probability that a vehicle being designated is a tank.

A third method of determining the a priori probabilities would be by observing designator operators under simulated battlefield conditions and counting the number of times they designated actual targets and the number of times they designated false targets.

Finally, two comments on the a priori probabilities and misclassification cost seem in order. First, both the probabilities and cost are likely to depend on the tactical situation in which the identification aid is being used. Secondly, because the cost and probabilities enter into the discriminant function as products, it is not necessary to know the probabilities more accurately than the misclassified cost. Because the costs are estimates, the rough estimates of the probabilities should also be sufficient.

E. Advantages of the Discriminant Function

The chief advantage in using the discriminant function for target classification is the ease with which it can be implemented. Although a considerable amount of data and extensive computations are required to construct the discriminant function, this computation can be performed on a high-speed computer. Once the discriminant function has been found and programmed into the identification aid, all that remains is the evaluation of a linear (or, at worst, quadratic) function and comparing the value of the function with a constant. Thus, "on board" computation is kept to a minimum. In fact, the entire decision process can probably be implemented in a single microcircuit.

VI. RECOMMENDATIONS FOR AN EXPERIMENTAL RESEARCH PROGRAM

It is clear from the preceding discussion that a considerable amount of experimental data is needed before the feasibility of a laser target identification system can be fully assessed. Even more data will be required to implement such a system. In this section, recommendations are presented for an experimental program which is considered to be the logical next step in the development of a laser designator target identification aid. Recommendations are made in the following paragraphs.

Initial effort should be directed toward the use of vibration signatures for target identification. Additional discriminants can be considered later. The reason for recommending that vibration signatures be given first consideration is that previous analyses [5,6] indicate that they are the most likely to provide a positive means of target identification. Furthermore, the US Army Missile Research and Development Command (MIRADCOM) will have in the near future a CO₂ laser heterodyne detector system capable of sensing target vibrations. This measuring system can readily be adapted for studying target classification techniques.

The first step in the experimental program must be to provide a means of processing the audio output of the heterodyne detector to obtain quantities suitable for discriminant variables. An appropriate choice of variables would be to let X_i be the fraction of the total audio power in the frequency intervals from f_i to $f_i + \Delta f_i$. Note that it is not necessary for the frequency intervals to cover the entire spectrum. Also, it is permissible for them to overlap. There are several ways in which the power in a given frequency interval could be measured as follows:

- a) Using a spectrum analyzer.
- b) By means of a Doppler filter bank.
- c) By recording the audio, converting from analog to digital format, and then using a fast Fourier transform (FFT) algorithm to obtain the power spectrum.

Using a spectrum analyzer is impractical for mass data recording because its output will be in the form of a photograph of an oscilloscopic trace or a strip chart recording. Taking the data from the photograph and computing the power in various frequency intervals will involve an excessive amount of work.

The bank of Doppler filters is probably the simplest way to extract the data and is probably what would be used in an actual identification aid. But for experimental work, it has the disadvantage that the effect of changing the frequency intervals is to be investigated, the measurement must be repeated. This difficulty is avoided by use of the FFT because once the power spectrum has been computed and stored, it is a simple matter to have the computer compute as many different sets of (X_j) (corresponding to different frequency bands) as desired. Ideally, all three systems should be available: a spectrum analyzer for "quick look" data, digital data for the bulk of the data collection, and a Doppler filter bank for implementing a prototype.

The first data collected should be a "quick look" at the vibration spectrum of a number of vehicles in order to determine the range of frequencies which will be encountered and to obtain a general impression of the shape of the power spectral density curves. These data could be collected using a spectrum analyzer.

On the basis of the observed power spectra, a number of frequency bands should be selected for further study. These bands should be chosen in that region of the spectra where there appears to be the greatest difference between different types of vehicles. Now, a large number of measurements should be made on two or three different vehicle types and the power in each band recorded. These data should be analyzed to determine the following:

- a) The average (\bar{X}_j) in each frequency band.
- b) The variance of the X_i .
- c) The probability density function of each X_i in order to verify the assumption of normal distribution.

The last of these can be done using a chi-square test or, more crudely, by plotting the cumulative distribution function on probability paper.

The purpose of these measurements is (1) to verify (or reject) the assumption of normal distributions; (2) to test the assumption that the covariance matrix will be the same for targets and nontargets (the assumption is supported if the variances are the same for different type vehicles); and (3) to determine if the discriminant variable is likely to be useful for classification. This is done by comparing the difference in means for various vehicle types with the variance. The larger the difference in means, the more likely the variable is to be effective in classification. Conversely, if there is no detectable difference in the mean from one type vehicle to another, then the variable is useless for classification.

The objectives of these measurements can be accomplished by using only a small number of frequency bands (two to five) and a few vehicle types (two to three). However, to obtain reasonable statistics, a large number of individual measurements (at least 50 and preferably 100) should be made on each vehicle.

The next step should be to repeat the preceding measurement using different frequency bands, and various bandwidths. If the original probability density functions (PDF) have been stored in a computer, the frequency bands can be changed without actually repeating the measurement. After a number of bands have been investigated, there should be a reasonably good indication whether or not there is a sufficient difference in the vibration spectra to allow classification, and if so, what frequency band should be used.

Assuming that frequency bands have been found in which there is a significant difference in target and nontarget means, an attempt can now be made to construct a discriminant function and perform target classifications. This can best be done by means of a computer simulation. The procedure is as follows:

a) On the basis of the previous results, a set of frequency bands are selected. Then, using the available data (and additional data, if needed), the coefficients of the discriminant function are computed.

b) A computer is programmed to evaluate the discriminant function and make the classification decision. The computer is then given sets of data taken from both targets and nontargets; the number of misclassifications is determined. If the data consist of N_1 targets and N_2 nontargets, the a-priori probabilities are taken as follows

$$P_T = \frac{N_1}{N_1 + N_2}$$

and

$$P_{\bar{T}} = \frac{N_2}{N_1 + N_2}$$

and the misclassification costs are assumed to be equal. The misclassification error rate (MER) is then

$$MER = \frac{N_{mc}}{N_1 + N_2}$$

where N_{mc} is the number of incorrect classifications.

c) The computer simulation can be used to investigate the effect of varying the number, center frequency and bandwidth of the frequency bands used to obtain the discriminant variables.

Once an adequate discriminant function is found, it will remain only to implement and test a prototype identification aid. The circuitry required is shown in the Figure. The output of the optical heterodyne detector is demodulated and passed through a bank of Doppler filters. The input of the filter bank is held constant by an automatic gain control (AGC) circuit so that the rectified outputs of the filters are proportional to the variables X_j . Each output is amplified by an amount proportional to its coefficient in the discriminant function. The output of the amplifier is then summed to yield the discriminant function. Classification is then performed by a threshold detector which determines if the discriminant function exceeds a preset level. This circuitry is very simple and could easily be constructed in hours.




Figure. Filter bank detectors.

REFERENCES

1. Webb, W. E., A Comparative Analysis of Laser Terminal Homing Systems Operating in the 2- to 10- μ m Wavelength Region, US Army Missile Command, Redstone Arsenal, Alabama, 16 May 1975, Report No. TR-RE-75-29 (CONFIDENTIAL).
2. Webb, W. E., Emmons, G. A., and Pratt, H. L., Laser Semiactive Terminal Homing, US Army Missile Command, Redstone Arsenal, Alabama, July 1975, Report No. TR-RE-76-2 (CONFIDENTIAL).
3. Webb, W. E., Widenhofer, G. H., and Emmons, G. A., Active Laser Terminal Homing, US Army Missile Command, Redstone Arsenal, Alabama, July 1975, Report No. TR-RE-76-4 (CONFIDENTIAL).
4. Webb, W. E., Emmons, G. A., and Pratt, H. L., Atmospheric Attenuation of Laser Radiation, US Army Missile Command, Redstone Arsenal, Alabama, July 1975, Report No. TR-RE-76-25 (CONFIDENTIAL).
5. Webb, W. E., Active Infrared Techniques for Aid for Target Identification, US Army Missile Command, Redstone Arsenal, Alabama, 1976 (UNCLASSIFIED).
6. Webb, W. E., Measurement of Vibration Signatures by Means of a CO₂ Laser, US Army Missile Command, Redstone Arsenal, Alabama, October 1976 (UNCLASSIFIED).
7. Anderson, T. W., An Introduction to Multivariate Statistical Analysis, New York: John Wiley and Sons, 1958.
8. Morrison, D. F., Multivariate Statistical Methods, New York: McGraw Hill, 1967.
9. Wald, A., "On the Statistical Problem Arising in the Classification of an Individual into One of Two Sets," Am. Math. Stat., Volume 15, 1945, p. 145.
10. John, S., "Errors in Discrimination," Ann. Math. Stat., Volume 32, 1961, p. 1125.
11. Box, G. P. E., "Some Theorems of Quadratic Norms Applied in the Study of Analysis of Variance Problems, I. Effects of Inequality of Variance in the One-Way Classification," Ann. Math. Stat., Volume 25, 1954, p. 290.

DISTRIBUTION

	No. of Copies
Defense Documentation Center Attn: DDC-TGA Cameron Station Alexandria, Virginia 22314	12
Commander US Army Research Office P. O. Box 12211 Research Triangle Park North Carolina 27709	1
Headquarters DA (DAMA-ARZ) Washington, D. C. 20310	1
Director of Defense Research and Engineering Engineering Technology Washington, D. C. 20301	1
Director Defense Advances Research Projects Agency 1400 Wilson Boulevard Arlington, Virginia 22209	1
Commander US Army Electronics Command Attn: DRSEL-CT, Dr. R. Buser Fort Monmouth, New Jersey 07703	1
Director US Army Night Vision Laboratory Fort Belvoir, Virginia 22060	1
Commander US Army Harry Diamond Laboratory 2800 Powder Mill Road Adlphi, Maryland 20723	1
Commander US Air Force Avionics Laboratory Attn: R. Becker AFAL/RWM-2 LT COL Gagnon AFAL/RWM-2 Wright Patterson Air Force Base, Ohio 45433	1 1

No. of
Copies

Raytheon Company
Attn: A. V. Jelalian
528 Boston Post Road
Sudbury, Massachusetts 01776

1

Chief of Naval Research
Department of the Navy
Washington, D. C. 20360

1

Science and Technology Division
Institute of Defense Analysis
Attn: Dr. Vincent J. Corcoran
400 Army-Navy Drive
Arlington, Virginia 22202

1

Environmental Research Institute of Michigan
Radar and Optics Division
Attn: Dr. A Kozma
P. O. Box 618
Ann Arbor, Michigan 4107

1

Commander
US Naval Weapons Center
Attn: Code 3517, Mr. Leonard Hauger
China Lake, California 93555

2

Superior Technical Services, Inc.
Attn: T. Ward
4308 Governors Drive
Huntsville, Alabama 35805

DRSMI-LP, Mr. Voigt

1

DRDMI-X, Dr. McDaniel

1

-T, Dr. Kobler

1

-TE, Mr. Lindberg

1

Mr. Todd

1

Mr. Pittman

1

-TEO, Mr. Ducote

1

Mr. Pratt

1

Dr. Curtis

15

-TR, Dr. Hartman

1

-TBD

3

-TI (Record Set)

1

(Reference Copy)

1